

Uncontrolled document as of March 7, 2011. Refer to website for up to date specifications.

CASES 1650 Case



1650 Case

- Retractable extension handle
- 4 strong polyurethane wheels with stainless steel bearings
- Easy open Double Throw latches
- Open cell core with solid wall design - strong, light weight
- O-ring seal
- Automatic Pressure Equalization Valve
- Fold down handles
- Stainless steel hardware and padlock protectors
- 2 level Pick N Pluck™ with convoluted lid foam
- [Personalized nameplate service available](#)
- Lifetime Guarantee of Excellence
- Watertight, crushproof, and dust proof

1650 Case Configurations

Cat. #	Description
1650	1650 Case
1650NF	1650 Case (No foam)
1654	1650 Case with Padded Dividers



Black



OD Green*



Desert Tan

*OD Green available upon request (minimum quantities apply)

1650 Case Specifications

Exterior Dimensions (L x W x D)		Interior Dimensions (L x W x D)	
31.59" x 20.47" x 12.45" (80.2 x 52 x 31.6 cm)		28.57" x 17.52" x 10.65" (72.5 x 44.5 x 27 cm)	
<i>This case has internal wheel and/or handle wells that will reduce usable area. Please review for each application.</i>			
Lid Depth	Bottom Depth	Total Depth	
1.81" (4.6 cm)	8.84" (22.4 cm)	10.65" (27 cm)	
Weight with foam	Weight without foam	Buoyancy Max.	
28.06 lbs. (12.73 kg)	24.03 lbs. (10.9 kg)	181 lbs. (82.1 kg)	
Range Temperature	No. of Wheels		
-40 / 210° F (-40 / 99° C)	4		

Personalized Nameplate Available

1650 Case Certificates

- IP67 (1 meter submersion for 30 minutes)
- MIL C-4150J • Def Stan 8 1-41/STANAG 4280 • ATA 300

1650 Case Accessories

Cat. #	Description
1651	4 pc. Replacement Foam Set
1652	Pick N Pluck™ Sections Only (set of 2)
1653	Replacement O-ring
1655	Padded Divider Set Only
1659	Photo/Lid Organizer for 1650 Case

Pelican Products, Inc.

23215 Early Avenue • Torrance, CA 90505 • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311
e-mail:sales@pelican.com • www.pelican.com