

Uncontrolled document as of March 11, 2011. Refer to website for up to date specifications.



Submersible

MityLite™ 1900 Flashlight

Unlike conventional flashlights that have a yellowish beam, the MityLite 1900 flashlight uses a hi-intensity Xenon lamp that produces a powerful, bright beam. Use this compact flashlight to cut through thick smoke, fog, and dust. It is submersible and comes with a twist-on shroud. The 1900 is ideal for any situation. Powered by 2 AAA alkaline cells.

Minimum Pack 6 ea.
Packaged Weight: 2.4 oz.

MityLite™ 1900 Flashlight Specifications

	High
LIGHT SOURCE	Xenon
BATTERIES	2 AAA Alkaline (Included)
CHARGE TIME	N/A
VOLTAGE	3
LENGTH	4.09" (10.4 cm)
WEIGHT w/ BATTERIES	1.6 oz. (0.05 kg)
WEIGHT w/o BATTERIES	0.75 oz. (0.02 kg)

MityLite™ 1900 Flashlight Configurations

Cat. #	Description
1900	MityLite™ 1900 Flashlight (Carded)
1900T	MityLite™ 1900 Flashlight (Clear Gift Tube)
1900M	MityLite™ 1900 Flashlight Merchandiser Display

NSN List

NSN #	Description
6230-01-365-7647	1900T Orange
6230-01-463-8505	1900C
6230-01-522-3357	1900C Yellow
6230-01-281-3774	1900LM
6230-01-345-6314	1900T Black
6230-01-324-2950	1900T Orange
6230-01-518-2061	1900TNVG Black
6240-01-428-9410	1904 Lamp Module

MityLite™ 1900 Flashlight Accessories

Cat. #	Description
722	Helmet Light Holder
1904	MityLite™ 1900 Lamp Module

	FL1 STANDARD	High
LIGHT OUTPUT		11 LUMENS
RUNTIME (hours/min)		1h 30m
BEAM DISTANCE (meters)		45m
PEAK BEAM INTENSITY (candela)		571cd
WATER RESISTANT		

MityLite™ 1900 Flashlight Approvals

Class I, Div. 2; Gp ABCD, T3C; Class II; Div. 2; Gp G.

IECEx

Ex ib e IIC T4 IP67 IEC Ex TSA06.0021X



Class I, Div. 1, GP C,D, T3C CONFORMS TO STD UL 783

Pelican Products, Inc.

23215 Early Avenue • Torrance, CA 90505 • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311
e-mail:sales@pelican.com • www.pelican.com