

Uncontrolled document as of March 11, 2011. Refer to website for up to date specifications.

LIGHTS
1965
MityLite LED



MityLite™ 1965 LED Flashlight

YOUR WORLDWIDE PASSPORT THROUGH HAZARDOUS LOCATIONS

While working in hazardous locations, remember a flashlight can be an ignition source. When you need the latest and brightest LED technology in a compact form factor, choose the new MityLite™ 1965 LED from Pelican. Small enough to fit in your shirt pocket, yet bright enough to illuminate your work area.

Long lasting, energy efficient, bright LEDs, along with a compact package make the new MityLite™ 1965 LED the safety approved light for the job.

MityLite™ 1965 LED Flashlight Specifications





	High	
LIGHT SOURCE	LED	
BATTERIES	2 AAA Alkaline (Included)	
CHARGE TIME		
VOLTAGE	3	
LENGTH	5.48" (13.9 cm)	
WEIGHT w/ BATTERIES	1.9 oz. (0.05 kg)	
WEIGHT w/o BATTERIES	1.1 oz. (0.03 kg)	

MityLite™ 1965 LED Flashlight Configurations

Cat. #	Description
1965	MityLite™ 1965 LED Flashlight (Carded)

MityLite™ 1965 LED Flashlight Accessories

Cat. #	Description
722	Helmet Light Holder

	FL 1 STANDARD	High	
LIGHT OUTPUT		21 LUMENS	
RUNTIME (hours/min)		4h	
BEAM DISTANCE (meters)		51m	
PEAK BEAM INTENSITY (candela)		756cd	

MityLite™ 1965 LED Flashlight Approvals



II 1 GD Ex ia IIC T4 Ga Ex iaD 20 IP65 T90°C Da
Certificate: TRAC10ATEX11241X



IECEx TRC10.0005X - II 1 GD Ex ia IIC T4 Ga Ex iaD 20 IP65 T90°C



Class I II III Div. 1 Grps. ABCDEFG T4



Class I II III Div. 1 Grps. ABCDEFG T4

Pelican Products, Inc.

23215 Early Avenue • Torrance, CA 90505 • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311
e-mail:sales@pelican.com • www.pelican.com